



KP-7500 keypad Specifications

Construction		<p>durable, premium grade polycarbonate enclosure resistant to extreme temperatures, water, and grease</p>
Input Surface		<p>20-key membrane, each rated for 30 million pushes metal reinforced top for extended life</p>
Mounting Options		<p>removable rubber feet for table top or wall mounting cost-effective bracketing options</p>
Overlay Options		<p>customizable keypad overlays, installed without tools</p>
Features		<p>software programmable scan code definitions adjustable sound for frequency and volume downloadable firmware for updates ConnectSmart ControlPoint support</p>
Physical	Dimensions	1.25 x 8.25 x 2.75 (H x W x D inches)
	Weight	10.4 ounces
	Connectors	1 Mini DIN, 1 Mini-B USB
	Sound	on-board annunciators
Power	Requirements	provided by controller
Environmental	Operating Temperature	0 to 60° C
	Storage Temperature	-20 to 95° C
	Humidity	10% to 95%, non-condensing
	Altitude	15,000 feet
Connections	Connection Type	PS/2 or USB
	Cable	6-pin Mini DIN or Mini-B USB
	Distance Span	100 feet PS/2 or 15 feet USB
Safety and Certifications	FCC	Class A, Part 15
	CE	EN55024
		WEEE, EU RoHS, MIC, China RoHS